HD 4/11 C BP PACK

First battery powered professional high-pressure cleaner HD 4/11 C Battery. For mobile applications, like, e.g. in the municipal area or in landscaping. Incl. 2x 36 V lithium-ion batteries.













Order no.

1.520-926.0

- Independent high-pressure cleaning irrespective of external power sources
- High cleaning performance with long runtime
- Two powerful 36 V lithium-ion batteries included in the scope of supply

| Technical data | | |
|--|-----------|---------------------------------|
| EAN code | | 4054278355306 |
| Battery platform | | 36 V battery platform |
| Flow Rate | l/h | 320 - 400 |
| Water feed temperature | °C | 60 |
| Operating pressure | bar / MPa | 70 - 110 / 7 - 11 |
| Max. Pressure | bar / MPa | 150 / 15 |
| Power rating | kW | 1.6 |
| Water feed | | 3/4" |
| Battery type | | Lithium-ion replacement battery |
| Voltage | V | 36 |
| Capacity | Ah | 7.5 |
| Number of batteries required | Piece(s) | 2 |
| Runtime per battery charge | min | 30 (7.5 Ah) |
| Battery charging time with fast charger 80%/100% | min | 58 / 81 |
| Charging current | Α | 6 |
| Power supply for battery charger | V / Hz | 100 - 240 / 50 - 60 |
| Cable length of battery charger | m | 1.2 |
| Weight (with accessories) | kg | 26.9 |
| Weight incl. packaging | kg | 31.2 |
| Dimensions (L × W × H) | mm | 380 × 370 × 930 |
| | | |

| Equipment | | |
|----------------------------|----|------------------------------|
| Variant | | Battery and charger included |
| Trigger gun | | EASY!Force |
| High-pressure hose | m | 10 |
| Spray lance | mm | 840 |
| Triple nozzle (0°/25°/40°) | | manual |
| Dirt Blaster spray lance | | • |
| Pressure switch control | | • |
| Suction hose | | |
| Included in delivery. | | |



36 V battery platform

- High cleaning performance and long runtimes.
- Compatible batteries across several ranges.
- Time-saving quick charger.

Economical and efficient ecolefficiency mode

- Saves energy and extends the runtime of the battery.
- Reduced cleaning performance for lighter dirt.

Quality

- The automatic pressure relief protects the components and extends the service life.
- High-quality brass cylinder head.
- Large, easily accessible water fine filter for protecting the pump against dirt particles in water.



























| * |
|----|
| 14 |

| | | Order no. | Description | |
|---|----|-------------|--|---|
| BATTERIES | | | | |
| Battery Power+ 36/75 | 1 | 2.445-043.0 | | |
| Battery Power+ 36/60 | 2 | 2.042-022.0 | | |
| BATTERY CHARGERS | | | | |
| Fast battery recharger Battery Power+ 36/60 | 3 | 2.445-047.0 | | |
| TRIGGER GUNS | | | | |
| EASY!Force Advanced | 4 | 4.118-005.0 | Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero. | - |
| Conversion kit 1 from high pressure hose | 5 | 4.111-050.0 | A conversion kit which enables secure connection from an M22 hose onto our innovative EASY!Force trigger gun. The kit includes the EASY!Force Trigger gun, adaptors and lance. | |
| Conversion kit 2 from device | 6 | 4.111-051.0 | Provides all the parts required to utilise our EASY!Force technology even on our non-Easy!Force machines. Including adaptors, lance, Easy!Force trigger gun and hose. | |
| Conversion kit 3 only EASY!Force | 7 | 4.111-052.0 | A conversion kit for the EASY!Force gun, which includes the correct adaptors to connect to the M22 style lance and hose. | |
| SPRAY LANCES | | ' | | |
| Rotating spray lances | | | | |
| Spray lance, 840 mm, rotatable | 8 | 4.112-006.0 | 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | - |
| LED nozzle light | 9 | 2.680-002.0 | LED work light for assembly on EASY!Force spray lances, providing a clear view in poor lighting conditions ensuring controlled cleaning results. | |
| Spray lance, 250 mm, rotatable | 10 | 4.112-027.0 | 250 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |
| Spray lance, 400 mm, rotatable | 11 | 4.112-024.0 | 400 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |
| Spray lance, 600 mm, rotatable | 12 | 4.112-007.0 | 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |
| Spray lance, 1050 mm, rotatable | 13 | 4.112-000.0 | 1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |
| Spray lance, 1550 mm, rotatable | 14 | 4.112-018.0 | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |

 $[\]blacksquare$ Included in delivery. \qed Available accessories.

EQUIPMENT FOR HD 4/11 C BP PACK 1.520-926.0



























| | | | | Τ |
|--|----|-------------|---|-----|
| | | Order no. | Description | |
| SPRAY LANCES | | oraci no. | - Section | + |
| Rotating spray lances | | | | _ |
| Spray lance, 2050 mm, rotatable | 15 | 4.112-021.0 | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | |
| Spray lance extender, 1000 mm | 16 | 4.112-048.0 | Spray lance extension with EASY!Lock connection. Length 1000 mm. | [|
| Double lance | | | | İ |
| Double lance, 960 mm | 17 | 2.112-016.0 | 960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning). | |
| Angular spray lance | | ' | | |
| WC and gutter lance | 18 | 4.112-029.0 | Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets. | |
| Flexible spray lance | | | | |
| Flexible lance, 1050 mm | 19 | 4.112-035.0 | 1050 mm flexible lance with variable bend from 20° to 140° , ideal for cleaning difficult to reach areas, e.g. gutters. | |
| High pressure articulated joint | 20 | 4.112-057.0 | For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer. | |
| Gutter cleaner | | | | |
| Gutter cleaning lance | 21 | 2.112-015.0 | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the specia nozzle the gutter can be cleaned without removing the cover plates. | 1 [|
| Undercarriage spray lance | | | | |
| Underbody lance | 22 | 4.112-032.0 | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle. | |
| Additional handle | • | | | |
| Additional handle for EASY!Lock spray lances | 23 | 4.321-380.0 | Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task. | |
| PowerControl spray lance | | ' | | |
| Pressure regulating jet pipe packaged Po | 24 | 4.112-043.0 | | |
| ROTARY NOZZLES (DIRT BLASTERS) | | | | |
| Dirt Blaster, small | | | | |
| Dirt Blaster Nozzle, small, 028 | 25 | 4.114-056.0 | | ı |
| MULTIPLE-JET NOZZLES | | | | |
| Triple nozzles | | | | |
| Triple Nozzle, 028 | 26 | 4.117-024.0 | Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. | • |
| HIGH-PRESSURE HOSES | | | | |
| Standard with unions on both sides | | | | |
| High-pressure hose, 10 m, DN 6, 250 bar, | 27 | 6.110-034.0 | 10 m high-pressure hose (M 22 × 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar. | F |

■ Included in delivery.

□ Available accessories.



















| | | | | _ |
|---|----|-------------|---|-----|
| | | | | |
| | | Order no. | Description | |
| HIGH-PRESSURE HOSES | | | | |
| Standard with unions on both sides | | | | |
| High-pressure hose, 10 m, DN 6, 300 bar, 2 × EASY!Lock | 29 | 6.110-056.0 | With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22×1.5 with anti-kink protection. NW $6/155^{\circ}$ C/300 bar | 5 🗆 |
| High-pressure hose, 10 m, DN 8, 315 bar, 2 × EASY!Lock | 30 | 6.110-031.0 | 10 m high-pressure hose (M 22×1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar. | |
| High-pressure hose, 15 m, DN 8, 315 bar, 2 × EASY!Lock | 31 | 6.110-030.0 | 15 m high-pressure hose (M 22×1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar. | |
| High-pressure hose, 20 m, DN 8, 315 bar, 2 × EASY!Lock | 32 | 6.110-032.0 | 20 m high-pressure hose (M 22×1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar. | |
| High-pressure hose, 30 m, DN 8, 315 bar, 2 × EASY!Lock | 33 | 6.110-014.0 | With rotary coupling, 2 × M 22 × 1.5 | |
| High-pressure hose, 15 m, DN 10, 220 bar, 2 × EASY!Lock | 34 | 6.110-042.0 | 15 m high-pressure hose M 22×1.5) with kink protection and threaded couplings at both ends. Further data: DN $10/155^{\circ}$ C/ 220 bar. | |
| High-pressure hose, 20 m, DN 10, 220 bar, 2 × EASY!Lock | 35 | 6.110-043.0 | with union on both sides, M 22×1.5 with anti-kink protection. NW $10/155^{\circ}$ C/220 bar | |
| High-pressure hose, 25 m, DN 10, 220 bar, 2 × EASY!Lock | 36 | 6.110-044.0 | | |
| High-pressure hose, 40 m, DN 10, 220 bar, 2 × EASY!Lock | 37 | 6.110-045.0 | | |
| High-pressure hose, 15 m, DN 12, 210 bar, 2 × EASY!Lock | 38 | 6.110-059.0 | High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. 2x M 22×1.5 with anti-kink protection. | |
| High-pressure hose, 40 m, DN 12, 210 bar, 2 × EASY!Lock | 39 | 6.110-060.0 | | |
| High-pressure hose, 10 m, DN 10, 220 bar, 2 × EASY!Lock | 40 | 6.110-041.0 | | |
| Longlife 400 with unions on both sides | | | | |
| High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, 2 \times EASY!Lock | 41 | 6.110-024.0 | 1.5 m high-pressure hose (DN 8, M 22×1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22×1.5). | |
| High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, $1 \times EASY!Lock / 1 \times M22 \times 1.5$ | 42 | 6.110-069.0 | High-pressure hose (ID 8) with double steel reinforcement, 1.5 m long, suitable for up to 400 bar pressure. Connectors: M 22 × 1.5, quick and convenient EASY!Lock hand screw connection. | |

 $[\]blacksquare$ Included in delivery. \qed Available accessories.























| | | Order no. | Description | |
|---|--------|-------------|--|---|
| HIGH-PRESSURE HOSES | | | | |
| Longlife 400 with unions on both sides | | | | |
| High-pressure hose Longlife, 10 m, DN 8, 400 bar, 2 \times EASY!Lock | 43 | 6.110-038.0 | Durable, 10 m long high-pressure hose (ID 8) with double steel reinforcement and EASY!Lock hand screw connection at both ends and ANTI!Twist. Approved for 400 bar pressure. | [|
| High-pressure hose Longlife, 30 m, DN 8, 400 bar, 2 \times EASY!Lock | 44 | 6.110-023.0 | With rotary coupling, 2 \times M 22 \times 1.5 | |
| High-pressure hose Longlife, 20 m, DN 8, 400 bar, $2 \times EASY!Lock$ | 45 | 6.110-027.0 | with rotary coupling, 2 \times M 22 \times 1.5 | [|
| High-pressure hose Longlife, 15 m, DN 8, 400 bar, 2 \times EASY!Lock | 46 | 6.110-029.0 | With rotary coupling, 2 × M 22 × 1.5 | |
| Food industry version with unions on both sid | es | | | İ |
| High-pressure hose food grade, 15 m, DN 6, 250 bar, 2 × EASY!Lock | 47 | 6.110-063.0 | 15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar. | |
| High-pressure hose food grade, 10 m, DN 8, 250 bar, 2 × EASY!Lock | 48 | 6.110-051.0 | 10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 \times 1.5 with anti-kink sleeve. | |
| High-pressure hose food grade, 20 m, DN 8, 250 bar, 2 × EASY!Lock | 49 | 6.110-052.0 | 20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22×1.5 , with kink protection. NW $8/155^{\circ}$ C/250 bar. | |
| Longlife food industry version with unions on | both s | ides | | |
| High-pressure hose food grade Longlife, 10 m, DN 8, 400 bar, 2 \times EASY!Lock | 50 | 6.110-053.0 | With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, ANTI!Twist and EASY!Lock hand screw connection at both ends. | |
| High-pressure hose food grade Longlife, 20 m, DN 8, 400 bar, $2 \times EASY!Lock$ | 51 | 6.110-054.0 | Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted) | |
| KÄRCHER POWER NOZZLE | | | | |
| Power nozzle spray angle 15° | | | | |
| Power Nozzle 15°, 028 | 52 | 2.113-041.0 | | |
| NOZZLE UNION / SPACER | | ' | | |
| Nozzle union | | | | |
| Nozzle screws | 53 | 4.112-011.0 | Nozzle screws with protectors for high-pressure and power nozzles | |
| PIPE CLEANING | | | | Ė |
| Pipe cleaning hose, ID 6 | | | | |
| Hose assembly TR pipe cleaning DN6 max.2 | 54 | 6.110-046.0 | The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8). | [|
| Pipe cleaning hose, DN 6, 20 m, 220 bar | 55 | 6.110-008.0 | $20\mathrm{m}$ flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R $1/8$ nozzle). | [|
| Hose assembly TR pipe cleaning DN6 max.2 | 56 | 6.110-047.0 | The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8). | |

[☐] Available accessories.

KÄRCHER























| PIPE CLEANING Pipe cleaning hose, ID 6 Hose assembly TR pipe cleaning DN6 14MPa Pipe cleaning hose | 57 | Order no. | Description | L |
|---|----|-------------------|--|---|
| ipe cleaning hose, ID 6 lose assembly TR pipe cleaning DN6 14MPa | | | | |
| lose assembly TR pipe cleaning DN6 14MPa | | 1 | | |
| | | 1 - 4 4 0 0 4 0 0 | | |
| ipe cleaning hose | 58 | 6.110-048.0 | 10 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle). | |
| | 50 | 6.110-049.0 | 20 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle). | |
| ipe cleaning hose, DN 6, 30 m | 59 | 6.110-050.0 | 30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle). | |
| ipe cleaning nozzle | • | | | |
| oirt blaster pipe cleaning D21/040 | 60 | 4.765-001.0 | The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted | |
| pirt blaster pipe cleaning D30/040 | 61 | 4.765-004.0 | -004.0 jets ensure the necessary forward movement, as well as convenient handling. | |
| LOOR AND HARD SURFACE CLEANER | | | | |
| lard surface cleaner FR 30 | | | | |
| R 30 Surface Cleaner | 62 | 2.111-011.0 | Up to 10 times greater area coverage compared with the conventional high pressure jet. | |
| lard surface cleaner FR 30 ME | | | | |
| R 30 ME surface cleaner | 63 | 2.111-013.0 | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. | |
| fachine-specific nozzle kit for FR | | | | |
| lozzle kit for FR, 400 l/h - 450 l/h | 64 | 2.641-457.0 | Machine-specific nozzle kit comprising power nozzles and screw connections. For the optimal performance of Kärcher surface cleaners (400-450 l/h). | |
| lozzle kit for FR, 450 l/h - 500 l/h | 65 | 2.640-482.0 | Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (450 to 500 l/h). | |
| OAM SYSTEMS | • | <u> </u> | | |
| up foam lance | | | | |
| up foam lance Basic 1, 350 l/h - 600 l/h | 66 | 4.112-053.0 | For high-pressure cleaners with a flow rate of 350-600 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent. | |
| -litre cleaning agent container for cup foam ance basic | 67 | 5.071-414.0 | | |
| -litre cleaning agent container for cup foam ance advanced | 68 | 6.414-050.0 | Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0). | |
| up foam lance Advanced 1, 400 l/h - 600 l/h | 69 | 4.112-063.0 | | Γ |
| up foam lance DUO Advanced 1, 400 /h - 600 l/h | 70 | 4.112-067.0 | | |

 $[\]hfill \square$ Available accessories.

KÄRCHER





























| | | | | Т |
|--|----|-------------|---|-----|
| | | 0 | Bookisting | |
| TO AN CYCTENIC | | Order no. | Description | _ |
| FOAM SYSTEMS | | | | |
| Inno Foam Set | 1 | 1 | luci e i su su i su como e como e como e como e como e como e como e como e como e como e como e como e como e | 1- |
| Inno foam kit with detergent injector | 71 | 2.112-000.0 | High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection. | |
| Easy Foam Set | | | | |
| Easy Foam Set with RM injector | 72 | 2.112-010.0 | HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately. | |
| Nozzle kits for Inno/Easy Foam Set | | | | |
| Nozzle kit 055 z. Inno/Easy Set 500 - 600 l/h $$ | 73 | 2.111-009.0 | Optimal adaptation to different machine outputs for economic use. | |
| Foam nozzle mounting kit | | | | |
| Foam nozzle kit | 74 | 2.112-013.0 | Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary. | |
| QUICK CONNECT | | | | |
| Quick-fitting pipe union coupler trapezo | 75 | 2.115-000.0 | For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread. | |
| Quick-fitting pipe union plug nipple tra | 76 | 2.115-001.0 | Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22×1.5 external thread. | |
| DRUM AND TANK CLEANING | | | | |
| Add-on kit mud sucker | 77 | 2.641-798.0 | | |
| OTHER HP ACCESSORIES | | | | |
| Add-on kit coin acceptor | 78 | 2.644-029.0 | Coin remote control with electronic coin acceptor for connecting a high-pressure cleaner as a pre-wash device. Please have the power outlet and cable provided on site. | |
| Jet gun | 79 | 2.869-067.0 | Short set-up time, easy transport, instant switch off – the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume. | |
| COUPLING PARTS | | | | |
| Rotary coupling | | | | |
| Rotary coupling | 80 | 4.111-021.0 | Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector Easy!Lock. With grip protection. | |
| Connector | | | | |
| Nozzle connector/screw connector | 81 | 4.111-022.0 | Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: $1 \times M$ 22×1.5 and $1 \times M$ 18×1.5 . | |
| Y distributor | 82 | 4.111-024.0 | Offers the option to connect two spray units to the machine. Installation on the high pressure outlet. | |
| Short spray unit | 83 | 4.111-038.0 | For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). No compatible with triple nozzles. | t 🗆 |
| Adapter EASY!Lock | | | | |
| Adapter 1 M22AG-TR22AG | 84 | 4.111-029.0 | Adapter 1 to connect the old hose with the new hose | |
| ☐ Available accessories. | | u . | | |

 $[\]hfill \square$ Available accessories.































| | | Order no. | Description | |
|--|----|-------------|--|--|
| COUPLING PARTS | | | | |
| Adapter EASY!Lock | | | | |
| Adapter 2 M22IG-TR22AG | 85 | 4.111-030.0 | Adapter 2 to connect the old device with the new hose and the old gun with the new hose | |
| Adapter 3 M22IG-TR22AG | 86 | 4.111-031.0 | Adapter 3 to connect the old gun with the new spray lance and new servo regulator | |
| Adapter M22 - Swivel | 87 | 4.111-032.0 | M22 \times 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection. | |
| Adapter 5 TR22IG-M22AG | 88 | 4.111-033.0 | Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance | |
| Adapter 6 TR22IG-M22AG | 89 | 4.111-034.0 | Adapter 6 to connect the new device with the old hose and the old hose with the new gun | |
| Adapter 7 M18IG-TR20AG | 90 | 4.111-035.0 | Adapter 7 to connect the old spray lance with the new nozzle | |
| Adapter 8 TR20IG-M18AG | 91 | 4.111-036.0 | Adapter 8 to connect the new spray lance with the old nozzle | |
| Coupler -2xM22x1,5 | 92 | 4.111-037.0 | Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2x \ M \ 22 \times 1.5 \ m$. | |
| ADAPTER for replacement TR22IG-M22AG Er | 93 | 4.111-046.0 | Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection | |
| HOSE REELS | | ' | | |
| Automatic, self-winding hose reels | | | | |
| Automatic plastic hose reel incl. high-pressure hose, 15 $\ensuremath{\text{m}}$ | 94 | 2.639-257.0 | | |
| Automatic hose reel, powder-coated steel / plastic, 20 m | 95 | 6.392-074.0 | Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic. | |
| Automatic stainless steel / synthetic material hose drum, 20 m | 96 | 6.392-083.0 | Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic. | |
| Automatic hose reel, coated, 20 m | 97 | 6.392-106.0 | Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose. | |
| Hose reel, automatic, basalt grey-coated, 20 m | 98 | 6.392-105.0 | Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. | |

 $[\]hfill \square$ Available accessories.



























| | | | | _ |
|--|-----|-------------|---|---|
| | | | | |
| | | Order no. | Description | |
| HOSE REELS | | | | |
| Automatic, self-winding hose reels | | | | |
| Automatic hose reel, stainless steel, includes swivel holder, 20 m | 99 | 6.392-076.0 | Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose. | |
| Automatic stainless steel hose reel, 40 m | 100 | 6.392-442.0 | Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit). | |
| Powder-coated swivel holder | 101 | 2.639-931.0 | Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel. | |
| Stainless steel swivel holder | 102 | 2.641-867.0 | Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose. | |
| FACADE AND SOLAR PANEL CLEANING | | | | |
| Brushes | | | | |
| Drive for roller brush 500 | 103 | 4.762-584.0 | Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance. | |
| Splash guard for roller brush 500 | 104 | 4.762-621.0 | Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time. | |
| Roller brush 500 soft | 105 | 4.762-623.0 | Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive. | |
| Roller brush 500 medium | 106 | 4.762-624.0 | Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system. | |
| Roller brush 500 hard | 107 | 4.762-625.0 | Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system. | |
| Brush hard | 108 | 6.960-133.0 | Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher. | |
| Brush medium | 109 | 6.960-134.0 | Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kårcher. | |
| Brush soft | 110 | 6.960-135.0 | For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems. | |
| Telescopic | | | | |
| TL low pressure adapter | 111 | 4.580-097.0 | TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes. | |
| Telescopic lance TL 7 F | 112 | 4.762-609.0 | Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension. | |

 $[\]hfill \square$ Available accessories.























| | | | | Т |
|---|-----|-------------|--|-------|
| | | 0 | Province to the state of the st | |
| FACADE AND SOLAR PANEL CLEANING | | Order no. | Description | 1 |
| Telescopic | | | | _ |
| Telescopic lance TL 7 H | 113 | 4.762-610.0 | Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix Telescopic thanks to quick-release fastenings. Up to 7 m reach. | . [|
| Telescopic lance TL 10 H | 114 | 4.762-611.0 | Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners. | ı |
| Telescopic lance TL 10 C | 115 | 4.762-612.0 | Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels. | [|
| Telescopic lance TL 14 C | 116 | 4.762-613.0 | Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners. | [|
| TL high pressure adapter | 117 | 4.775-154.0 | TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals. | [|
| WET BLASTING ATTACHMENT | | | | |
| Wet blasting attachment (without nozzle) | | | | |
| Wet blasting attachment with flow control (without nozzles) | 118 | 4.115-000.0 | Paint, rust and scale removal made easy: Kārcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. | [|
| Wet blasting attachment without flow control (nozzles not included) | 119 | 4.115-006.0 | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control. | [|
| Nozzle pack for wet blasting attachment | | ' | | |
| Nozzle pack TR wet jet set 0035 | 120 | 2.112-021.0 | Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.115-000.0 4.115-006.0. | [|
| Boron carbide nozzle | • | | | |
| Boron carbide nozzle, for machines as of 1000 $\ensuremath{I/h}$ | 121 | 6.415-084.0 | In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation. | |
| WATER CONNECTION | | | | |
| Geka coupling | | | | |
| With hose nozzle, R 1/2" | 122 | 6.388-461.0 | with hose liner | [|
| With hose nozzle, R 3/4" | 123 | 6.388-455.0 | | [|
| With hose nozzle, R 1" | 124 | 6.388-465.0 | with hose barb | [|
| With female thread, R 3/4" | 125 | 6.388-473.0 | with female thread | 1 |
| Suction filter | | 1 | 1 | Ė |
| Water filter | 126 | 6.414-956.0 | Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 μm mesh, R 3/4" and R 1" connection, without non-return valve | 1 |

[☐] Available accessories.





















| | | Order no. | Description | |
|--|-----|-------------|---|----|
| WATER CONNECTION | | | | |
| Suction filter | | | | |
| Suction filter with check valve | 127 | 4.730-012.0 | Brass suction filter suitable for ponds, storage tanks, etc. With check valve. | |
| Fine-mesh water filter | | • | | |
| Add-on kit water filter universal | 128 | 2.637-020.0 | | |
| Fine-mesh water filter with adapter | 129 | 4.730-102.0 | Fine-mesh water filter, 125 μ m, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapte 1". | r, |
| Water supply hose | | | | |
| Water supply hose | 130 | 4.440-038.0 | NW 13 R1" / R 3/4", up to 30 °C | |
| | 131 | 4.440-207.0 | NW 19 R1" / R 3/4", up to 85 °C, for pick-up | |
| Backflow check valve | | | | |
| Backflow preventer | 132 | 2.641-374.0 | To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. – hot water resistant up to 80 $^{\circ}$ C – tested according to IEC 60335-2-79 – integrated leakage protection | |
| WASHING BRUSHES | | <u> </u> | | |
| Push-on washing brush | | | | |
| Push-on washing brush | 133 | 4.762-497.0 | With clamp for mounting directly to units' double or triple nozzle. Fits on new double and triple nozzles. | |
| Push-on wash brush, M 18 × 1.5 | 134 | 4.113-001.0 | Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 × 1.6. | [|
| Rotating washing brush | | • | | |
| Rotating wash brush for < 800 l/h machines, nylon bristles | 135 | 4.113-004.0 | The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 60° C. (M 18×1.5 , replaceable brush insert). | [|
| Rotating wash brush for < 800 l/h machines, natural bristles | 136 | 4.113-003.0 | Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60° C, M 18×1.5 (replaceable brush insert). | [|

[☐] Available accessories.