RAVAS-3200-F

Pallet truck scale with extended scale functions



BENEFITS


- Angled fork tips for easy access to low and closed pallets
- Automatic dosing function (option)
- Three communication protocols
- Internal clock for date/time
- For warehousing, dosing and mixing
- Bluetooth 4.0 for RAVAS WeightsApp

Top quality
Advanced functions













RAVAS-3200-F

FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic and manual tare
- Totalling with sequence number
- Code entry (5-digit)
- RS232 port for connection with printer
- Extra port for Bluetooth option board
- Bluetooth 4.0 for RAVAS WeightsApp
- Internal clock
- Error messages in display
- Automatic switch-of after 30 minutes of non-use
- kg/lb toggle

STANDARD SPECIFICATIONS

Weighing capacity 2.000 kg

Graduation multirange:

0 - 200 kg: graduation 0,2 kg 200 - 500 kg: graduation 0,5 kg 500 - 2.000 kg: graduation 1 kg

Max. tolerance
 0,1% of the load lifted

Display LCD, digit height 18 mm, backlight

Keypad 5 function keys, on/of key

Protection class
 load cells IP67, indicator IP65

Battery
 12Vdc/1.2Ah, exchangeable; battery

charger included (lead-acid)

Battery life 30 hours, low battery indication in

display

Charger 230V/12Vdc - 300 mACharging time approximately 6 hours


Steering wheels rubber

Loading wheels polyurethane, tandem

Colour red (RAL 3000), epoxy painted

Own weight 120 kgPump quick lift

DIMENSIONS IN MM



Α	Fork length	1150
В	Fork width	180
С	Minimum fork height	90
	Space underneath fork	22
D	Maximum fork height	210
	Lifting height	120
Ε	Width over forks	555
F	Height to top indicator	800
	Tolerance +/- 3 mm	





• ISO 9001 • ISO 1400

OPTIONS*

- Legal for trade version, OIML III
- Extra exchangeable battery pack
- Built-in thermal printer
- Bluetooth
- Relay setpoint switch for automatic dosing
- Multirange graduation 0,1/0,2/0,5 kg

- Stainless steel fork shoes
- Stainless steel or galvanized truck
- Pivoting indicator: readout from all angles during dosing
- Footbrake or handbrake
- Different fork dimensions (fork height 90 mm)
- Different steering or loading wheels



P.O. Box 2023, NL-5300 CA Zaltbommel, The Netherlands T. +31 (0)418 51 52 20, F. +31 (0)418 51 53 20 backoffice@ravas.com, www.ravas.com

